

HUAWEI Tecal RH2288H V2 Rack Server



Professional • Trusted • Future-oriented

Copyright © Huawei Technologies Co., Ltd. 2013. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice

 , HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd. Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-035260-20130502-C-2.0

enterprise.huawei.com

HUAWEI TECHNOLOGIES CO., LTD.



HUAWEI Tecal RH2288H V2 Rack Server

(RH2288H V2)

High performance and flexible scalability

- Supports two Intel® Xeon® E5-2600 /E5-2600V2 series processors, providing a maximum 12-core, L3 cache of 30 MB and QuickPath Interconnect (QPI) at 8 GT/s; adopts the power consumption adjustment and Turbo acceleration technology to improve performance while reducing power consumption.
- Supports 24 DDR3 DIMMs, with a maximum memory capacity of 768 GB, providing enriched memory resources for memory-intensive applications.
- Supports HUAWEI ES series high-performance PCIe SSD cards, providing superb I/O performance to resolve hard disk I/O bottlenecks.
- Supports high-performance GPUs, improving the graphics processing and floating-point computing performances.

High energy efficiency

- Uses highly efficient 80 Plus Platinum PSUs that comply with the ENERGY STAR standards and have passed the China Energy Conservation and Environmentally-Friendly Certification.
- Provides 460 W and 800 W PSUs for flexible configurations to improve power efficiency.
- Uses temperature sensors to monitor the heat of key components, working with intelligent fan speed adjustment to precisely cool the server, markedly increasing the cooling efficiency.
- Adopts dynamic power capping to control the preset power consumption, preventing service interruption.

Simple management and maintenance

- Supports the black box function to facilitate quick fault location and service recovery.
- Implements simple system management by using the built-in BMC, which supports SOL and remote KVM, startup, and shutdown.

Flexible and high reliability local storage

- Supports eight 2.5-inch SAS/SATA HDDs or SSDs. Alternatively, twelve 3.5-inch SAS/SATA HDDs and two 2.5-inch SAS/SATA HDDs or SSDs, or twenty-six 2.5-inch SAS/SATA HDDs or SSDs can be installed. Hard disks are hot-swappable. This meets the large storage capacity application
- Adopts the industry-leading RAID technology, supporting RAID 0, 1, 10, 5, 50, 6 and 60 and providing a 512 MB or 1 GB cache; supports an optional BBU and supercapacitor, RAID state migration, RAID configuration memory, self-diagnosis, and remote web setting to ensure data reliability.

Large memory and high performance



RH2288H V2 (26 hard disks)



RH2288H V2 (14 hard disks)



RH2288H V2 (8 hard disks)

The HUAWEI Tecal RH2288H V2 (RH2288H V2) is a new-generation 2U 2-socket rack server. Featuring two Intel® Xeon® E5-2600/ E5-2600V2 series processors, the RH2288 V2 provides a memory capacity of 768 GB and large storage capacity, making it an ideal product for critical services and cloud computing.

Technical Specifications

Form factor	2U rack server
Number of processors	1 or 2
Processor	Intel® Xeon® E5-2600 or E5-2600V2 series
Memory	24 DDR3 RDIMMs/LRDIMMs, up to 768 GB
Internal storage	Options: • 8 x 2.5" SAS/SATA HDDs or SSDs • 12 x 3.5" SAS/SATA HDDs and 2 x 2.5" SAS/SATA HDDs or SSDs • 26 x 2.5" SAS/SATA HDDs or SSDs
RAID support	RAID 0, 1, 10, 5, 50, 6, and 60 RAID cache: 512 MB or 1 GB Power-off protection: Supercapacitor
LOM network port	2 onboard GE ports or 4 onboard GE ports or 2 onboard 10GE ports
Expansion slot	Up to 7 PCIe 3.0 slots 1 processor: • (Optional 1) 1 PCIe 3.0 x16 and 1 PCIe 3.0 x8 • (Optional 2) 3 PCIe 3.0 x8 • 1 PCIe slot for a RAID controller card 2 processors: • 3 PCIe 3.0 x8 • 1 PCIe slot for a RAID controller card • (Optional 1) 1 PCIe 3.0 x16 and 1 PCIe 3.0 x8 • (Optional 2) 3 PCIe 3.0 x8
USB port	6 (front: 2, rear: 2, built-in: 2)
Fan module	4 hot-swappable counter-rotating fan modules in N+1 redundancy mode
PSU	2 hot-swappable 1+1 redundant PSUs: • AC: 460 W or 800 W • -48 V DC: 800 W
Management	BMC management module supports IPMI, SOL, KVM over IP, and virtual media One 10/100 Mbit/s RJ45 management network port
Operating systems supported	Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server Oracle Enterprise Linux / Oracle Server VM Debian CentOS Solaris Citrix XenServer VMware ESX / VMware ESXi Huawei FusionSphere
Power supply	110 V/220 V AC or -48 V DC
Operating temperature	5°C – 40°C (41°F – 104°F)
Dimensions	Height: 87.5 mm (3.44 in.) Width: 447 mm (17.60 in.) Depth: 740 mm (29.13 in.)